

## OTARIIDS/PHOCIDS SPLASH BASIC (SPLASH10-BF) SPECIFICATION

Tag Family	Model	Argos	Fastloc <sup>®</sup>	Temperature	Light Level	Life (days) <sup>1</sup>	L x W x H (mm)	Weight (g)
SPLASH	SPLASH10-BF-238	✓	✓	✓	Optional	470	105 x 56 x 30	213
SPLASH	SPLASH10-BF-296	✓	✓	✓	Optional	470	86 x 85 x 29	193
SPLASH	SPLASH10-BF-297	✓	✓	✓	Optional	240	86 x 55 x 26	130

<sup>1)</sup> The above estimated lives are calculated assuming 250 transmissions and 24 Fastloc® acquisitions per day. Utilizing the Wet/Dry sensor and duty cycling, the life can be extended.

These tags all feature the latest Fastloc\* technology for improved satellite acquisition and maximized battery and tag duration. They also incorporate tough urethane abrasion protection (body armor) and robust nitinol antennas.





Model: SPLASH10-BF-297



tags@wildlifecomputers.com WildlifeComputers.com +1 (425) 881-3048

8310 154th Ave NE, Suite 150 Redmond, WA, 98052 USA

This is a small representation of our available tags. Tag features and specifications subject to change without notice. Comparative scale is approximate. Argos antennas not shown to length. @ Wildlife Computers. All rights reserved.